Self-supervised deep learning models capture multi-dimensional features for cell morphology analysis from brightfield images

Kevin B. Jacobs, Kiran Saini, Nianzhen Li, Senzeyu Zhang, Ryan Carelli, Cris Luengo, Amy Wong-Thai, Anastasia Mavropoulos, Andreja Jovic, Thomas Vollbrecht, Jeanette Mei, Vivian Lu, Stephane C. Boutet, Mahyar Salek, Maddison Masaeli All authors are employed by Deepcell Inc. Menlo Park, CA, USA

BACKGROUND

- Morphology is a fundamental cell property associated with identity, state, & function, but there is a need for multi-dimensional, unbiased, & quantitative assessment.
- The Deepcell platform combines label-free brightfield imaging, deep learning, computer vision morphometrics, & gentle cell sorting to leverage multi-dimensional single cell morphology as a biological readout.
- Applications include high-throughput sample characterization, disease detection/enrichment, drug/functional screening, & multi-omic integration.

INTRODUCTION

- Deepcell's Human Foundation Model (HFM) is a hybrid architecture that combines self-supervised learning (SSL) & morphometrics (computer vision) to extract 119 dimensional embedding vectors representing cell morphology from high resolution Deepcell cell images. (Fig. 1)
- SSL produces a foundation model with high generalization capabilities that enables hypothesis-free sample exploration and efficient generation of application-specific models.
- Computer vision extracts features that represent measurable concepts and improves model interpretability.
 - e.g., cell size, shape, texture, intensity



Figure 1. HFM is a feature extractor. Features of cell images are encoded into multi-dimensional numerical vectors.

METHODS

Real-Time Image Processing

- Raw brightfield images of single cells are captured at up to 10,000 frames/sec and corrected for per-pixel variation in background offset, camera gain, & illumination.
- Cells are detected and tracked as they flow through a microfluidic channel.
- Each cell is segmented, cropped, & centered; the background normalized to a standard value.

Morphometric Features

Max Feret diameter Min Feret diameter Long/short axis



Figure 2. Examples of morphometric features. (A) Representative images showing 5 of 14 features describing cell shape and size. (B) Representative images showing 4 of 41 features describing pixel intensity and texture. Shown are morphometrics that describe size and intensities of "blobs", which relate to cellular structures like granules, vesicles.



Figure 3. Deepcell HFM training and inference architectures. (A) HFM training architecture. The backbone model, which extracts image features, is based on the ResNet18 convolutional deep neural network architecture. Training combines VICReg self-supervised learning, which learns image features without labels, with orthogonal morphometric features to improve model performance and interpretability. (B) Loss terms minimized during HFM training. (C) HFM evaluation architecture. The ResNet18 backbone trained in (A) and the morphometric feature encoder are applied along with custom trained classification heads to generate embedding vectors and classify cells. Calculations are performed on the Deepcell instrument using Nvidia A6000 GPUs, Intel Xeon CPUs, and a custom FPGA to identify and sort cells in realtime. (D) HFM hyperparameters, training dataset details, and inference latency.

Model performance evaluation

HFM performance was evaluated using two simple datasets comprising multiple known cell types mixed *in silico*. For each dataset, a random forest classifier head was trained on HFM embeddings to predict cell class and evaluated using an independent set of images.

- Figure 4: mixture of four synthetic cell types ranging from 20-40 µm diameter that simulate cell features (used as a reference control sample) • Classification accuracy is 100% with several highly interpretable features driving classification.
- Figure 5: mixture of 6 µm beads and three cancer cell lines • Classification accuracy is high with biological samples of similar size distributions and features.

Visit our other posters:

- Deepcell Platform [5381]
- 2. Deepcell AI & Data Science [5361]
- Heterogeneous Tumor Subpopulation Enrichment [2392]
- 4. Melanoma Phenotype Classifier [5926]
- 5. Malignant Effusion Tumor Cell Enrichment [LB170]



nce between two embeddings nented images of the same cell red.
nce of each embedding n over a training batch of images ned above a threshold.
iances between pairs of g dimensions over a training mages are minimized.
iances between pairs of g and morphometric

dimensions over a training batch of images are minimized.

əl	ResNet 18
	~11 million
	4,013,508
	814
	35
	119 total 64 AI + 55 morphometrics
	0.95 ms/ image

Learn more: www.deepcell.com



Predicted cell class

explainability.



Figure 5. Evaluation of mixed cell types. 6µm polystyrene beads and three cancer cell lines w/ distinct features were imaged on the Deepcell platform and combined in silico to evaluate HFM classification performance. (A) Table of cell classes, number of cell images analyzed, & representative images. (B) Morphology UMAP of 6µm beads and cancer cell lines colored by ground truth. (C) Confusion matrix: HFM predicts cell classes with high accuracy. (D) Density plots of top differential features by cell class. All cell lines have overlapping cell size distributions. A375 and Caov-3 are nearly identical in size, indicating that cell features other than size must be utilized to accurately differentiate A375 and Caov-3

CONCLUSIONS

- Combining deep learning and morphometric features improves accuracy and interpretability.
- HFM characterizes and classifies synthetic cells and biological samples with high accuracy. • Features beyond cell size are utilized.
- classification and sorting.
- tasks.

Cleepce

Figure 4. Evaluation of HFM synthetic cell classification. Synthetic cells with diverse structural features were imaged on the Deepcell platform. (A) Table of cell classes, number of images used for training and testing, & representative images of each class. (B) Morphology UMAP of HFM embeddings colored by ground truth. (C) Confusion matrix: HFM predicts synthetic cell class with 100% accuracy in all 4 classes. (D) Top differential morphometric and deep learning features. Utilizing both AI-derived features and computer vision features enhances model

• The Deepcell Human Foundation Model (HFM) is fast and effective at extracting cell features, enabling real time cell

• Real world applications of Deepcell's HFM include hypothesis-free sample exploration and adaptation to specific classification